


THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	9/9/03	P.PESA
B	ECN 5154: CREATE MODEL, NEW DRAWING FORMAT	11/18/10	D.FRISIELLO
C	ECN 6088: REVISE THREAD SIZE TO 3/8-32 UNEF-2A	4/12/12	D.FRISIELLO



△ 2X, 3/8-32 UNEF-2A

2X, TYPE F FEMALE CONNECTOR

GROUNDING TERMINAL
10 AWG MAX.

RoHS Compliant ✓

NOTES:

1. PROTECTOR MATERIAL:
BODY: ALUMINUM
CONTACT: GOLD PLATED BRASS
INSULATOR: PTFE
2. COMPONENTS SHALL BE PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATIONS.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm] OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0 >12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +3% / -0% ALL OTHER DIMENSIONAL TOLERANCES: .X = ±.2 .XX = ±.02 .XXX = ±.005	APPROVALS DRAWN BY D.FRISIELLO CHECKED BY K.BURGNER APPROVED BY K.BURGNER	DATE 11/18/10 11/18/10 11/18/10	45 BEECHWOOD DRIVE NORTH ANDOVER, MA 01845	
	CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY			CATEGORY LIGHTNING PROTECTOR PRODUCT DESCRIPTION LP,F-FEMALE TO F-FEMALE 3 GHz
PROJECTION 	COLOR VARIATIONS MAY OCCUR	SIZE A	FSCM NO. 43321 DWG. NO. AL-FFFF	REV. C
		SCALE: NONE	CAD FILE: AL-FFFF.SLDDRW	SHEET 1 OF 1