


8 7 6 5 4 3 2 1

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	10/25/13	D.GRIFFIN
B	ECN 8758: ADDED DIMENSION FOR PANEL MOUNT	5/8/17	D.FRISIELLO



"P1"
2X, SERIES "A"
USB 3.0 PLUG
CONTACTS: 30μINCHES
GOLD PLATING

2X, L-COM LOGO
ONE SIDE

"P1"	WIRING MAP	"P2"
1	RED	1
2	WHITE	2
3	GREEN	3
4	BLACK	4
5	BLUE	8
6	YELLOW	9
7	DRAIN WIRE	7
8	PURPLE	5
9	ORANGE	6
SHELL	BRAID	SHELL

2X, MOLDED HOOD
AND STRAIN RELIEF
PVC, BLUE (300C)

MODEL NUMBER	LENGTH METERS [FEET]
CAVISU3AA-03M	0.3 [.98]
CAVISU3AA-05M	0.5 [1.64]
CAVISU3AA-1M	1.0 [3.28]
CAVISU3AA-2M	2.0 [6.56]
CAVISU3AA-3M	3.0 [9.84]
CAVISU3AA-5M	5.0 [16.41]

NOTES:

CABLE: UL STYLE 20276, 2X, TWISTED PAIR, 30AWG WITH ALUM/POLY FOIL SHIELD AND DRAIN WIRE. ONE UNSHIELDED TWISTED PAIR, 30AWG. 2 COND., 24AWG. OVERALL BRAID SHIELD, 65% JACKET: PVC, BLUE (PANTONE 300C)

MISCELLANEOUS:

CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY. CABLE ASSEMBLY SHALL HAVE 360° SHIELD TERMINATION. CABLE ASSEMBLY MUST MEET USB 3.0 REQUIREMENTS. CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031.

REGULATORY COMPLIANCE:
CE2011/65/EU(RoHS DIRECTIVE)

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm] OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0 >12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +3% / -0%	APPROVALS	DATE		45 BEECHWOOD DRIVE NORTH ANDOVER, MA 01845
	DRAWN BY D.FRISIELLO	6/3/13		CATEGORY
ALL OTHER DIMENSIONAL TOLERANCES: .X = ± .2 .XX = ± .02 .XXX = ± .005	CHECKED BY D.DESJARDIN	6/3/13	PRODUCT DESCRIPTION	CA USB3.0 A/A W/HDWARE VISION 3.0
PROJECTION 	APPROVED BY S.SMITH	6/3/13	CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY	SIZE A FSCM NO. 43321 DWG. NO. CAVISU3AA REV. B
	COLOR VARIATIONS MAY OCCUR		SCALE: NONE	CAD FILE: CAVISU3AA.SLDDRW SHEET 1 OF 1