

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

RoHS Compliant ✓


REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	9/23/10	D.GRIFFIN
B	ECN 5210: ADDED WIRE MAP, HARDWARE NOTES & HOOD DIMS., DETAIL VIEW	12/15/10	

D



C

B

A





"P1"
DB15 MALE
CONNECTOR



"J1"
DB15 FEMALE
CONNECTOR

WIRE MAP		
"P1"	COLOR	"J1"
1	BLACK	1
2	BROWN	2
3	RED	3
4	ORANGE	4
5	YELLOW	5
6	GREEN	6
7	BLUE	7
8	PURPLE	8
9	GRAY	9
10	WHITE	10
11	PINK	11
12	LT. GREEN	12
13	BLACK/WHITE	13
14	BROWN/WHITE	14
15	RED/WHITE	15
SHELL	DRAIN	SHELL



THIS DETAIL VIEW TYPICAL
MALE/FEMALE

MODEL NUMBER	LENGTH	
	FEET	METERS
CPMS15MF-1	1.0	.30
CPMS15MF-2.5	2.5	.76
CPMS15MF-5	5.0	1.52
CPMS15MF-10	10.0	3.05
CPMS15MF-25	25.0	7.62
CPMS15MF-50	50.0	15.24

NOTES:

SUPPLIED WITH THUMBSCREWS IN PLACE.
NOTE: SUPPLIED WITH OPTIONAL USE HARDWARE AND INSTRUCTIONS.
CABLE INTERCONNECTION HARDWARE: (4) SCREWLOCKS, H= .191"
PANEL MOUNT HARDWARE: (4) SCREWLOCKS, H= .160"

CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY.

CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm] OVERALL CABLE LENGTH TOLERANCE: $\le 12 [305] = +1 [25] / -0$ >12 [305] $\le 60 [1524] = +2 [51] / -0$ >60 [1524] $\le 120 [3048] = +4 [102] / -0$ >120 [3048] $\le 300 [7620] = +6 [152] / -0$ >300 [7620] = +3% / -0%	APPROVALS	DATE		45 BEECHWOOD DRIVE NORTH ANDOVER, MA 01845
	DRAWN BY D.FRISIELLO	9/7/10		CATEGORY DATA CABLING
ALL OTHER DIMENSIONAL TOLERANCES: .X = ± .2 .XX = ± .02 .XXX = ± .005	CHECKED BY S.SMITH	9/7/10	PRODUCT DESCRIPTION 20 AWG D-SUB CABLE ASSEMBLY	
PROJECTION 	APPROVED BY S.SMITH	9/7/10	SIZE A	FSCM NO. 43321
	CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY		DWG. NO. CPMS15MF	REV. B
	COLOR VARIATIONS MAY OCCUR		SCALE: NONE	CAD FILE: CPMS15MF.SLDDRW
			SHEET 1 OF 1	