	REVISIONS						
REV	DESCRIPTION	DATE	APPROVAL				
Α	DRAWING REPLACES CS9-OD1	7/3/14	D.FRISIELLO				

MODEL NUMBER	PRIMARY PACKAGING	SECONDARY PACKAGING	LENGTH	
CS9-100	COIL	BOX	100.0 FEET	
CS9-500	SPOOL	STRETCH WRAP	500.0 FEET	
CS9-1K	SPOOL	STRETCH WRAP	1,000.0 FEET	

CONDUCTOR SIZE: 24 AWG. (7/32) TINNED COPPER.

SHIELDING: ALUMINUM/MYLAR FOIL SHIELD AND 24 AWG. TINNED STRANDED COPPER DRAIN WIRE.

NOMINAL DIAMETER: 0.230 IN.

JACKET: CHROME GRAY PVC.

RATINGS: 300V, 80°C UL2464

COLOR CODE				
CONDUCTOR	COLOR			
1	BLACK			
2	WHITE			
3	RED			
4	GREEN			
5	BROWN			
6	BLUE			
7	ORANGE			
8	YELLOW			
9	PURPLE			

REGULATORY COMPLIANCE: CE2011/65/EU(ROHS DIRECTIVE)

	APPROVALS	DATE	_			/		
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm]	DRAWN BY B.DAGGETT	7/14/00	Ŀ	C		Global Connec	NORTH AT	NOOD DRIVE NDOVER, MA
OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / - 0	CHECKED BY D.PARHAM	7/14/00	CATEGO	RY		CONTINUE	0	1845
>12 [305] - 60 [1524] = +2 [51] / -0 >60 [1524] - 120 [3048] = +4 [102] / -0 >120[3048] - 300[7620] = +6 [152] / -0	APPROVED BY R.CARRICK	7/14/00	D-SUBMINIATURE					
>300[7620] = +5% / -0% ALL OTHER DIMENSIONAL TOLERANCES: .X = .2 [5.08] .XX = .005 [.13]	CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY		PRODUCT DESCRIPTION BULK CBL, 9 CON #24					
PROJECTION (+)	COLOR VARIA MAY OCC		SIZE	FSCA 433		DWG. NO.	CS9	A REV.
			SCALE:	1:1	CAD F	FILE: CS9.SLDDRW		SHEET 1 OF 1