THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT WRITTEN PERMISSION OF L-COM, INC IS PROHIBITED.

REVISIONS							
REV	DESCRIPTION	DATE	APPROVED				
A	INITIAL RELEASE	6/14/13	D.FRISIELLO				
В	ECN 7144: REMOVED OUTDOOR FROM CABLE DESCRIP. REVISED DWG # AND DESCRIP.	11/8/13	D.DESJARDIN				

TABLE						
FOBOM1Z-M	62.5/125 micron A-Series Micro Multimode OFNR (Riser) Rated Duplex Zip cord Cable. Jacket: PVC, 2.0mm Jacket Color: Orange					

## General Characteristics for Riser Rated (OFNR) Duplex Fiber Cables

UL Listing: UL1666

Minimum Bend Radius:

Under Installation: 3.8 cm (1.5 in) Under Long-Term: 2.5 cm (1.0 in)

Operating Temperature: -40°C to +85°C (-40° F to +185° F)

Storage Temperature: -55°C to +85°C (-67° F to +185° F)

Max. Tensile Load lbs: Short Term 135 lbs Long Term 67 lbs

Optical Performance: Max Attenuation dB/km:

1310nm 1.5 dB/km 850nm 3.5 dB/km

Impact Resistance: 750 Impacts

Crush Resistance: 500 N/cm

## These specifications are subject to change without prior notification.

Cable lengths 50 meters and under will be secured with twist-tie, and packaged per L-Com specification PS-0031.

Cable lengths over 50 meters will be spooled with 5' pigtails.

		L-COM	Global Connectivity	45 Beechwood Drive North Andover, MA 01845		
		DRAWING TITLE				
DRAWN BY	DATE	OM1 2mm Duplex OFNR ORG				
D.FRISIELLO	6/14/13					
CHECKED BY	DATE		DRAWING NUMBER		REV.	
D.DESJARDIN	6/14/13	SIZE	FO	BOM1Z-M	В	
APPROVED BY	DATE	A	FILE NAME		SHEET	
D.GALLAGHER	6/14/13		FC	DBOS1Z-M.DOC	1 OF 1	