


THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	4/6/12	D.GRIFFIN



NOTES:
 MATERIAL: NICKEL PLATED BRASS.
 CONNECTOR ASSEMBLY POLISH TYPE: PC.
 MODEL IS LOCKING STYLE, MULTIMODE.
 STRIP FIBER CABLE TO MIL-STD-2042-5B. STRIP DIMENSIONS ARE +/- 1mm.
 DUST CAP IS INSTALLED FOR SHIPMENT.
 COMPONENTS COME UNASSEMBLED AND SHALL BE INDIVIDUALLY PACKAGED IN A POLY BAG.

RoHS Compliant ✓

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm] OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0 >12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +3% / -0% ALL OTHER DIMENSIONAL TOLERANCES: .X = ±.2 .XX = ±.02 .XXX = ±.005	APPROVALS DRAWN BY D.FRISIELLO	DATE 2/28/12		45 BEECHWOOD DRIVE NORTH ANDOVER, MA 01845		
	CHECKED BY D.GUITADAURO APPROVED BY D.GALLAGHER	DATE 2/28/12 2/28/12		CATEGORY FIBER OPTICS		
PROJECTION 	CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY	PRODUCT DESCRIPTION MIL ST MM LOCKING NPB 2MM	SIZE A	FSCM NO. 43321	DWG. NO. FOC-M83522-ANXB	REV. A
COLOR VARIATIONS MAY OCCUR		SCALE: NONE	CAD FILE: FOC-M83522-ANXB.SLDDRW	SHEET 1 OF 1		