

6

5

4

3

2

1

## LENGTH


## OPTICAL SPECIFICATION

## REVISION




LENGTH (L) METER [FEET]	TOLERANCE MM [INCHES]
5 [16.40]	+50/-0 [+1.97/0]
10 [32.81]	+100/-0 [+3.94/0]
20 [65.62]	+1%*L/-0
30 [98.43]	+1%*L/-0

FIBER TYPE	MULTIMODE
CONNECTOR TYPE	IP-MPO/UPC
INSERTION LOSS	≤ 0.5dB
RETURN LOSS	≥ 25dB
TEST WAVE LENGTH	850 & 1550nm

ZONE	REV	DESCRIPTION	DATE	CHANGED BY	APPROVED
	B	ECO-13297	02/08/2024	DZINN	PHOSPODAR



VIEW A-A

12F MPO POLARITY:  
METHOD B, KEY DOWN-KEY DOWN

VIEW B-B

## NOTES:

1. MPO CONNECTOR ASSEMBLY POLISH TYPE: UPC.
2. MPO POLARITY: TIA METHOD B.
3. ALL CONNECTORS INCLUDE PROTECTIVE DUST CAPS.
4. CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IAW L-COM SPECIFICATION PS-0031.

REGULATORY COMPLIANCE:  
EU RoHS DIRECTIVE (MOST RECENT RELEASED VERSION)

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INFINITE ELECTRONICS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF INFINITE ELECTRONICS, INC. IS PROHIBITED. THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

UNLESS OTHERWISE SPECIFIED  
LEADING DIMENSIONS ARE INCHES  
DIMENSIONS IN [ ] ARE MILLIMETERS

TOLERANCES:  
X = ±.2 [5] FRACTIONS ± 1/32  
.XX = ±.02 [0.5] ANGLES ± 1°  
.XXX = ±.005 [0.13]

CABLE LENGTH TOLERANCES:  
≤12 [305] = +1 [25] / -0  
>12 [305] ≤ 60 [1524] = +2 [51] / -0  
>60 [1524] ≤ 120 [3048] = +4 [102] / -0  
>120 [3048] ≤ 300 [7620] = +6 [152] / -0  
>300 [7620] = +5% / -0

ALL DIMENSIONS ARE FOR REFERENCE ONLY  
AND SUBJECT TO CHANGE WITHOUT NOTICE.  
UN-DIMENSIONED/NON-CRITICAL FEATURES  
MAY VARY IN SIZE AND LOCATION  
COLORS MAY VARY

**L-com**  
an INFINIT@ brand

Website: [www.L-com.com](http://www.L-com.com)  
Phone: 1.800.341.5266 | 1.978.682.6936



INTERPRET ALL DIMENSIONS AND  
TOLERANCES PER ASME Y14.5

SCALE	SHEET
NONE	1 OF 1

## DESCRIPTION

IP68 OUTDOOR CABLE ASSY, 5MM OD, OM4, MPO/UPC MALE  
12F TO MPO/UPC MALE 12F, TYPE B

SIZE	CAGE CODE	DRAWN BY	ITEM NO.	REV
A	43321	DZINN	FOCM40DMPMB12	B

6

5

4

3

2

1