I THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

8

D

С

R

	0	Z	1	I	
		REVISIONS			-
REV		DESCRIPTION		DATE	APPROVED
А	INITIAL RELEASE			09/27/12	D.GRIFFIN
	-		DESCRIPTION	EV DESCRIPTION	EV DESCRIPTION DATE

PRODUCT SPECIFICATIONS PRODUCT: COAX-SEAL PACKAGING:

7

60" consumer rolls, 1/2" wide, in-retail packaging for pegboard or counter display.

5

- (12) industrial rolls, 1/2" wide or 1" wide. 4 ROLLS PER BOX
- Pre-cut strips, 1/2" wide, in 10" and 4" lengths, bulk-packed.
- \cdot 10" strip or (2) 4" strips in envelope, with complete instructions for use.

6

DESCRIPTION:

Easily applied, hand-moldable, tacky black plastic mastic, on peel-away paper backing, suitable for waterproofing a wide variety of connections. Adheres to vinyl and PVC outer jackets. Product is non-conductive, non-contaminating and non-toxic, and UV-stable.

APPLICATIONS:

Provides a long-lasting, waterproof seal for coaxial cable fittings and many other connections. Use for TV and radio antennas, satellite dishes, CATV, wireless networks, marine electronics, feed lines, radar and microwave installations, and many other applications.

VISCOSITY:

ASTM D5-52, gm load, 5 sec.=7.0/10.0 mm. Non-hardening, non-oxidizing at ambient temperature.

TEMPERATURE RANGE:

Apply between 40° F. to 110° F. **PERCENT SOLIDS:**

98%

SOLVENTS:

None

OTHER PROPERTIES:

Material is non-staining to paint; stays flexible and maintains a waterproof seal over an extreme range of temperatures. Will not crack at -200° F, will not slump 1 hr. @350° F.

OPTIMUM CURE CYCLE:

Not curable

RoHS Compliant 🗸







С