

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISIONS

REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	9/22/15	D.GRIFFIN

15.31 [389]

12.75 [323.8]

10.00 [254]

Ø.32 MOUNTING HOLES (4X)

11.8 [300]

13.8 [351]

10.9 [276]

12.8 [324]

14.75 [374.6]

304 SS PIANO HINGE

HIDDEN LINES REPRESENT COMPONENTS ON BACK OF PLATE -DO NOT DRILL-

14.75 [374.7] MOUNTING HOLES

316 SS PADLOCKABLE LATCHES Ø.375 PADLOCK EYE

NOTE:

- ENCLOSURE MATERIAL-BLACK HOT MOLDED FIBERGLASS REINFORCED POLYESTER
- NEMA RATED TYPE 3, 3R, 3S, 4, 4X, 12 AND 13 PRIOR TO MODIFICATIONS.
- ICE 529 RATED IP 66 PRIOR TO MODIFICATION.
- TEMPERATURE RANGE FROM -50 DEG C TO 150 DEG C.
- SELF EXTINGUISHING AND HALOGEN FREE.
- CABINETS ARE MAINTENANCE FREE AND CORROSION RESISTANT.
- SHALL BE PACKAGED AS PER L-COM SPEC PKG-00070
- ALL DIMENSIONS FOR REFERENCE ONLY.

REGULATORY COMPLIANCE:
CE2011/65/EU(RoHS DIRECTIVE)

1/2" CONDUIT CONNECTOR

SEE DETAIL "A" (2X)

GROUND LUG

4.25(2x)

3.50(2x)

1.75

0

1.75

3.80

8.58

10.25 REF.

3.2 [83]

2.4 [61]

1.1 [28]

13.3 [338]

5.7

3.90 [99.1]

DETAIL "A"

Ø.625

Ø.578

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm]

DIMENSIONAL TOLERANCES:

X = ±.1 [2.54]
XX = ±.01 [.25]
XXX = ±.005 [.13]

ANGULAR TOLERANCES:

ALL = ± 1°

PROJECTION

APPROVALS

DATE

DRAWN BY
B.PUCHASKI

CHECKED BY
P.PESA

APPROVED BY
P.PESA

09/01/15

09/01/15

09/01/15

CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY

COLOR VARIATIONS MAY OCCUR

SCALE: NONE

CAD FILE: NBB141207-10V.SLDDRW

SHEET 1 OF 1

ENCLOSURE

PRODUCT DESCRIPTION
NEMA ENCLOSURE 14 X 12 X 7 WEATHERPROOF 120VAC VENTED, BLACK

SIZE
A

FSCM NO.
43321

DWG. NO.
NBB141207-10V

REV.
A

45 BEECHWOOD DRIVE
NORTH ANDOVER, MA
01845

The drawing includes a front view (top left) showing the enclosure with two large rectangular cutouts and four mounting holes. A side view (top right) shows the enclosure with two padlockable latches. A bottom view (bottom left) shows the base of the enclosure with a ground lug and conduit connector. A detail view (bottom center) shows a cross-section of the enclosure wall. A 3D perspective view (bottom right) shows the enclosure with its lid open. Dimensions are given in inches and millimeters. A table of revisions is at the top right. A table of approvals and dates is at the bottom right. A table of product information is at the bottom right. A table of regulatory compliance is at the bottom left.

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISIONS

REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	9/22/15	D.GRIFFIN

15.31 [389]

12.75 [323.8]

10.00 [254]

Ø.32 MOUNTING HOLES (4X)

11.8 [300]

13.8 [351]

10.9 [276]

12.8 [324]

14.75 [374.6]

304 SS PIANO HINGE

HIDDEN LINES REPRESENT COMPONENTS ON BACK OF PLATE -DO NOT DRILL-

14.75 [374.7] MOUNTING HOLES

316 SS PADLOCKABLE LATCHES Ø.375 PADLOCK EYE

NOTE:

- ENCLOSURE MATERIAL-BLACK HOT MOLDED FIBERGLASS REINFORCED POLYESTER
- NEMA RATED TYPE 3, 3R, 3S, 4, 4X, 12 AND 13 PRIOR TO MODIFICATIONS.
- ICE 529 RATED IP 66 PRIOR TO MODIFICATION.
- TEMPERATURE RANGE FROM -50 DEG C TO 150 DEG C.
- SELF EXTINGUISHING AND HALOGEN FREE.
- CABINETS ARE MAINTENANCE FREE AND CORROSION RESISTANT.
- SHALL BE PACKAGED AS PER L-COM SPEC PKG-00070
- ALL DIMENSIONS FOR REFERENCE ONLY.

REGULATORY COMPLIANCE:
CE2011/65/EU(RoHS DIRECTIVE)

1/2" CONDUIT CONNECTOR

SEE DETAIL "A" (2X)

GROUND LUG

4.25(2x)

3.50(2x)

1.75

0

1.75

3.80

8.58

10.25 REF.

3.2 [83]

2.4 [61]

1.1 [28]

13.3 [338]

5.7

3.90 [99.1]

DETAIL "A"

.625

.578

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm]

DIMENSIONAL TOLERANCES:

X = ±.1 [2.54]
XX = ±.01 [.25]
XXX = ±.005 [.13]

ANGULAR TOLERANCES:

ALL = ±1°

PROJECTION

APPROVALS

DATE

DRAWN BY
B.PUCHASKI

CHECKED BY
P.PESA

APPROVED BY
P.PESA

09/01/15

09/01/15

09/01/15

CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY

COLOR VARIATIONS MAY OCCUR

SCALE: NONE

CAD FILE: NBB141207-10V.SLDDRW

SHEET 1 OF 1

45 BEECHWOOD DRIVE
NORTH ANDOVER, MA
01845

L-com Global Connectivity

CATEGORY

ENCLOSURE

PRODUCT DESCRIPTION

NEMA ENCLOSURE 14 X 12 X 7 WEATHERPROOF 120VAC VENTED, BLACK

SIZE

A

FSCM NO.


43321

DWG. NO.

NBB141207-10V

REV.

A

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm] DIMENSIONAL TOLERANCES: $.X = \pm .1$ [2.54] $.XX = \pm .01$ [.25] $.XXX = \pm .005$ [.13]	APPROVALS	DATE	 45 BEECHWOOD DRIVE NORTH ANDOVER, MA 01845			
	DRAWN BY B. PUCHASKI	09/01/15			CATEGORY ENCLOSURE	
	CHECKED BY P. PESA	09/01/15	PRODUCT DESCRIPTION NEMA ENCLOSURE 14 X 12 X 7 WEATHERPROOF 120VAC VENTED, BLACK			
APPROVED BY P. PESA	09/01/15	CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY		SIZE A	FSCM NO. 43321	DWG. NO. NBB141207-10V
ANGULAR TOLERANCES: $ALL = \pm 1^\circ$	COLOR VARIATIONS MAY OCCUR		SCALE: NONE		CAD FILE: NBB141207-10V.SLDDRW	SHEET 1 OF 1
PROJECTION 