




THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

RoHS Compliant ✓

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	RELEASED FOR PRODUCTION	4/30/01	DFP
B	ECN 6795: REVISED CONTACTS TO 30u", NEW FORMAT, PACKAGING	4/15/13	D.FRISIELLO



WIRING CHART	
LEAD COLOR	"J1"
BLUE	1
ORANGE	2
BLACK	3
RED	4
GREEN	5
YELLOW	6
BROWN	7
WHITE	8

NOTES:

- MOLDED PARTS ARE 94V-0 PLASTIC, ABS, GRAY.
- CONTACTS HAVE 30 MICRO INCHES OF GOLD PLATE.
- STRANDED COPPER LEADS ARE COLOR CODED.
- ADAPTER KIT MAY BE PROGRAMMED AS NEEDED BY INSERTING AND SEATING EACH MALE CONTACT IN THE DESIRED POSITION IN THE D-SUB SHELL.
- D-SUB FRAME SNAPS SECURELY INTO HOUSING.
- RJ45 SHIELDING IS TIED TO D-SUB SHELL.
- ADAPTER KIT IS SUPPLIED UN-ASSEMBLED, IN A LOGO BAG PER L-COM SPECIFICATION PS-0031.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm] OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0 >12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +3% / -0% ALL OTHER DIMENSIONAL TOLERANCES: .X = ±.2 .XX = ±.02 .XXX = ±.005	APPROVALS DRAWN BY D PARHAM CHECKED BY T CLARK APPROVED BY R CARRICK	DATE 4/17/2001 4/24/2001 4/30/2001	45 BEECHWOOD DRIVE NORTH ANDOVER, MA 01845	
	CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY COLOR VARIATIONS MAY OCCUR			CATEGORY TELECOM/MODULAR PRODUCT DESCRIPTION ADAPTER DB9M TO RJ45 SHLD JACK
PROJECTION 	SIZE A	FSCM NO. 43321	DWG. NO. RS9EMI8M	REV. B
SCALE: NONE		CAD FILE: RS9EMI8M.SLDDRW		SHEET 1 OF 1