


THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
E	ECN 4944: ADDED FRONT & BACK SHELL FINISH, ADDED PKG NOTE, DEL CURRENT RATING	8/3/10	D. CASTRO
F	ECN 7987: UPDATED NOTES TO MATCH SUPPLIER SPEC	6/16/15	D. CASTRO
G	ECN 8860: ADD 'REACH' COMPLIANCY NOTE	7/19/2017	R. CLARK
-	-	-	-



NOTES:

MATERIAL:

CONNECTOR SHELL: STEEL
 CONNECTOR INSULATOR: THERMOPLASTIC, UL94V-0 RATED
 CONTACTS: BRASS

FINISH:

FRONT SHELL: NICKEL PLATED
 BACK SHELL: TIN PLATED
 CONTACTS: 5 µin SELECTIVE GOLD
 SOLDER CUPS: TIN PLATED

ELECTRICAL:

DIELECTRIC WITHSTANDING VOLTAGE: 1000 VAC rms
 INSULATION RESISTANCE: 500MΩ @ DC 500V
 CONTACT RESISTANCE: 25 MILLIOHMS MAX
 CURRENT RATING: 1 AMP

MISCELLANEOUS:

OPERATING TEMPERATURE: -55°C TO +105°C
 CONNECTOR SHALL BE PACKAGED IN ACCORDANCE WITH L-COM SPEC PS-0031.

REGULATORY COMPLIANCE:

CE2011/65/EU (RoHS DIRECTIVE)
 REACH REGULATION (EC) No 1907/2006

CATALOG #	PACKAGING
SD9S	1/BAG
SD9S-TRAY	50/TRAY

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm] OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0 >12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +3% / -0%	APPROVALS	DATE		45 BEECHWOOD DRIVE NORTH ANDOVER, MA 01845
	DRAWN BY B.MAZEJKA	11/10/2003		
ALL OTHER DIMENSIONAL TOLERANCES: .X = ±.2 .XX = ±.02 .XXX = ±.005	CHECKED BY C.McCORMICK	12/08/2003	CATEGORY D-SUBMINIATURE	
	APPROVED BY D.PARHAM	12/08/2003	PRODUCT DESCRIPTION FEMALE DB9F SOLDER CUP CONNECTOR	
PROJECTION 	CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY	COLOR VARIATIONS MAY OCCUR	SIZE A	FSCM NO. 43321
			DWG. NO. SD9S	REV. G
	1AC08-017	SCALE: NONE	CAD FILE: SD9S.SLDDRW	SHEET 1 OF 1