

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE
PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR
WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC.
IS PROHIBITED

REVISIONS									
REV	DESCRIPTION	DATE	APPROVAL						
Α	DRAWING REPLACES SPV332-38-OD1 AT REV A	12/17/14	D.FRISIELLO						





SPECIFICATIONS:

GENERAL PURPOSE, IRRADIATED POLYOLEFIN FIT®-221= 2:1 SHRINK RATIO
MIL-DTL-23053/5C,
CLASS 1, 2
UL STANDARD 224
CSA STANDARD 198
COLOR; BLACK

PACKAGING: 100 PIECES PER BAG.

REGULATORY COMPLIANCE: CE2011/65/EU(ROHS DIRECTIVE)

	APPROVALS	DATE				2011 45 0555010	
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm]	DRAWN BY R.CARRICK	8/12/2004	Ŀ			Coppectivity NORTH AN	NOOD DRIVE NDOVER, MA
OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / - 0	CHECKED BY ENG	8/12/2004	CATEGORY 018		1845		
>12 [305] - 60 [1524] = +2 [51] / -0 >60 [1524] - 120 [3048] = +4 [102] / -0 >120[3048] - 300[7620] = +6 [152] / -0	APPROVED BY C.MCCORMICK	8/12/2004	CAILOC	/K I		D-SUBMINIATURE	
>300[7620] = +5% /-0% ALL OTHER DIMENSIONAL TOLERANCES:	CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY		PRODUCT DESCRIPTION SHRINK, 3/32"ODX3/8"L 100/PK				
PROJECTION (+)	COLOR VARIATIONS MAY OCCUR		SIZE	FSCA 43	и NO. 321	DWG. NO. SPV332-38	A REV.
			SCALE:	8:1	CAD F	ILE: SPV332-38.SLDDRW	SHEET 1 OF 1