8 7 6 5 4 4 3 2 1

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REV DESCRIPTION DATE APPROVED

A INITIAL RELEASE 1/9/13 D.GRIFFIN



	KIT DETAIL					
QTY	ITEM					
1	PLASTIC UTILITY BOX (NOT SHOWN)					
1	2 IN 1 MODULAR CRIMP TOOL					
20	RJ12 (6X6) PLUG, RECTANGULAR ENTRY					
20	RJ12 (6X6) PLUG, RADIUS ENTRY					
20	RJ45 (8X8) PLUG, RECTANGULAR ENTRY					
20	RJ45 (8X8) PLUG, RADIUS ENTRY					

NOTES:

8

D

1. CRIMP TOOL CAN CRIMP RJ11/12 AND RJ45 PLUGS

7

2. COMPONENT SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031.

	UNLESS OTHERWISE SPECIFIED,	APPROVALS	DATE	I _		NEIT	- Siglobal		OOD DRIVE	
DIMENSIONS ARE IN INCHES [mn		DRAWN BY				ו ־ויע	Connec	ctivity NORTH AND	- ,	
	OVERALL CABLE LENGTH TOLERANCE:	D. DESJARDIN	11/5/12		-		00111100	018	345	
	≤12 [305] = +1 [25] / -0 >12 [305] ≤60 [1524] = +2 [51] / -0	D. FRISIELLO	11/6/12	CATE	GORY					٦.
	>60 [1524] <120 [3048] = +4 [162] / -0 >120 [3048] <300 [7620] = +6 [152] / -0	APPROVED BY		TELECOM/MODULAR						
	>120 [3048] <300 [7620] = +6 [152] / -0 >300 [7620] = +5% / -0%	D. GALLAGER	11/8/12	122200111/1110202711						
	ALL OTHER DIMENSIONAL TOLERANCES:	CONFIGURATION DETAILS OF		PRODUCT DESCRIPTION						
	$.X = \pm .2$ $.XX = \pm .02$ $.XXX = \pm .005$	UNDIMENSIONE MAY V	O FEATURES	CRIMP TOOL KIT, RJ45 & RJ11/12						
PROJECTION		COLOR VARIATIONS		SIZE	FSCM 422		DWG. NO.		RE	. 1
	(\oplus) \leftarrow $ +$	MAY OCCUR		A 43321		4 I	TCK68MOD		<i>F</i>	1
				SCA	ALE: NONE	CAD FIL	E: TCK68MOD).SLDDRW	SHEET 1 OF	1
	Δ									