


THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	02/05/04	MCCORMICK
B	ECN4278: ADDED OPERATING TEMPERATURE RANGE AND PACKAGING	9/30/09	D.FRISIELLO
C	ECN 5602: FIX TO SCALE	7/13/11	D. CASTRO



RoHS Compliant ✓

NOTES:

1. IP (INGRESS PROTECTION) RATING: 67.
2. OPERATING TEMPERATURE RANGE: -40°C TO +105°C.
3. COMPONENT SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm] DIMENSIONAL TOLERANCES: .X = ±.1 .XX = ±.03 .XXX = ±.005 ANGULAR TOLERANCES: ALL = ± 1°	APPROVALS DRAWN BY C.MCCORMICK	DATE 02/05/2004		45 BEECHWOOD DRIVE NORTH ANDOVER, MA 01845	
	CHECKED BY D.PARHAM	02/05/2004			CATEGORY DATA CABLING
	APPROVED BY R.CARRICK	02/05/2004	PRODUCT DESCRIPTION DB15 MALE WATERPROOF SOLDER		
	CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY COLOR VARIATIONS MAY OCCUR	SIZE A	FSCM NO. 43321	DWG. NO. WPSD15P	REV. C
PROJECTION 		SCALE: NONE		CAD FILE: WPSD15P.SLDDRW	
			SHEET 1 OF 1		