




THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTIONS IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISIONS			
REV	DESCRIPTION	DATE	CHANGED BY
E	ECN 12067: REVISED NOTES, ADDED NOTE 5 (TORQUE), REVISED FORMAT	09/02/2022	GUITTADAURO




ONE 28AWG STRANDED TINNED COPPER TWISTED PAIR  
 TWO 24AWG STRANDED TINNED COPPER CONDUCTORS  
 OVERALL ALUMINIZED POLYESTER SHIELD WITH DRAIN WIRE  
 PLUS TINNED COPPER BRAIDED SHIELD.  
 PVC OUTER JACKET ,UV RESISTANCE , BLACK



PART NUMBER	LENGTH	
	METERS	FEET
WPUSBAXSH-05M	0.5	1.64
WPUSBAXSH-1M	1.0	3.28
WPUSBAXSH-2M	2.0	6.56
WPUSBAXSH-3M	3.0	9.84
WPUSBAXSH-5M	5.0	16.40

- NOTES:
1. THESE CABLE ASSEMBLIES ARE CONSTRUCTED TO MEET THE REQUIREMENTS OF THE UNIVERSAL SERIES BUS SPECIFICATION USB 2.0
  2. CONNECTOR CONTACTS HAVE 30 MICROINCHES GOLD PLATING OVER NICKEL PLATING.
  3. INGRESS PROTECTION RATING IS IP67 (J1 ONLY ,MATED)
  4. CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY.
  5. SUGGESTED MAX. TORQUE VALUE FOR HEX NUT IS 1.5N-m (13.2 lbf-in)
  6. CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM PACKAGING SPEC. PS-0031.

**REGULATORY COMPLIANCE:**  
 EU RoHS DIRECTIVE (MOST RECENT RELEASED VERSION)



RECOMMENDED PANEL OPENING

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES (mm). OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +5% / -0 ALL OTHER DIMENSIONAL TOLERANCES: .XX = ± .02 [5]      FRACTIONS ± 1/32 .XXX = ± .005 [13]      ANGLES ± 1°	APPROVALS	DATE	50 High Street, West Mill, North Andover, MA 01845 USA. Phone: 1.800.341.5266 1.978.682.6936	
	DRAWN BY	02/01/2010		CATEGORY: USB PRODUCT DESCRIPTION: CA IP67 USB-A-F/A-M SHLD
	CHECKED BY	02/01/2010		
	APPROVED BY	02/01/2010		
THIRD-ANGLE PROJECTION	COLOR VARIATIONS MAY OCCUR	SIZE: B CAGE CODE: 43321 ITEM NO.: WPUSBAXSH	REV: E SCALE: NONE CAD FILE: WPUSBAXSHLDRW SHEET 1 OF 1	