

HyperLink Wireless Brand 5.1-5.8 GHz Dual Polarity 13 dBi Omni-directional Antenna - Model: HG5158DP-13U

Features

- MIMO – Multiple-Input and Multiple-Output
- Dual Polarity feed system in single enclosure
- Dual polarity, high gain operation
- Two (2) integrated diversity antennas , single package
- UV-resistant radome for all-weather operation

Applications

- 5.1-5.8 GHz Outdoor Wireless LAN systems
- Supports 1x2 and 2x2 MIMO AP/Routers
- IEEE 802.11 a/n applications
- WiMax, WISP, WiFi, Communication
- Hospitality, Industrial, Municipality, MTU/MDU



Description

The HyperLink HG5158DP-13U Omni-directional Antenna combines vertical and horizontal polarization with high gain in a single enclosure. It is a professional quality antenna designed primarily for MIMO point-to-multipoint applications in the 5.1-5.8 GHz frequency band.

This antenna incorporates advanced dual polarization technology that allows for the interoperability of two radios transmit and receive paths. This technology allows for the attenuation of unwanted signals from adjacent channels and/or co-located equipment.



Specifications

Mechanical Specifications

Connectors	(2) Type N-Female
Dimensions (Diameter x Length)	Ø3.3 x 23.6 in (Ø84 x 600 mm)
Weight	4.4 lbs (2.0 kg)
Radome Material	UV Resistance PVC
Mounting	Ø1.6 – Ø2.4 in (Ø40 – Ø60 mm) Masts
Rated Wind Velocity	130mph (210km/h)
Wind Loading @ 100 / 125 / 150 mph	20 / 31 / 44 lbs
Operating Temperature	-40°C - +65°C (-40°F - +149°C)

Electrical Specifications

Frequency	5150-5850 MHz
Gain	13 dBi
VSWR	< 2.0:1
Polarization	Horizontal and Vertical
Horizontal Beam Width	360°
Vertical Beam Width	7°
Isolation	> 30 dB
Cross-polar Ratio	> 20 dB
Nominal Impedance	50 Ohms
Max. Input Power	100W
Lightning Protection	DC Ground (Vertical Pol Only)

HG5158DP-13U Antenna Pattern

