



RS485/422/232 Fiber modem

FRM220-Serial
FRM220-Serial-S

The FRM220-Serial/485 provides a fiber converter solution to extend asynchronous RS-485 or RS-232 transmission distance up to 2km over multimode fiber or up to 120km over single mode fiber. The converter is equipped with multiple interface circuits for connection to RS-232 or RS-485/422 (2 or 4 wire, full or half duplex). The FRM220-Serial secures data transmission over EMI resistant fiber at speeds up to 460kbps for RS-232 or up to 1024kbps for RS-485/422. When the FRM220-Serial/485 card is placed in the FRM220 rack with SNMP management, in-band management allows viewing the card and remote converter's status, type, version, fiber link status, data link status and alarms. Both card and remote can be configured to enable or disable the port, reset the port and set the interface type.

Features

- Extend asynchronous serial transmission from 2km to 120km over fiber
- In-band network management via terminal, web or SNMP in FRM220-CH20 chassis
- Software selectable data interface for RS232/ 422/ 485
- Software selectable two wires (half duplex) or four wires (full duplex) RS485
- Software selectable three or five wires RS232
- Speeds up to 256kbps for RS232 (Async. mode)
- Speeds up to 1Mbps for RS485/ 422

Optical Interface

Connector	1x9 (SC, ST, FC) or SFP LC
Data rate	36.864Mbps
Line coding	Scrambled NRZ
Bit Error Rate	Less than 10 ⁻¹⁰
Fiber	MM 62.2/125μm, 50/125μm, SM 9/125μm
Distance	MM 2km, SM 15/30/50/80/120km, WDM 20/40/60/80km
Wavelength	MM 1310nm, SM 1310, 1550nm, WDM 1310Tx/1550Rx(type A) 1550Tx/1310Rx(type B)

Electrical Interface

Connector	6 pins Terminal block
Data Signal	RS485 2-wire
Formats	RS422 4-wire RS232 RTS/CTS 5-wire RS232 3-wire
Baud Rate	RS422, RS485 up to 1024kbps RS232 up to 256kbps
Bit Error Rate	Less than 10 ⁻¹⁰
Standard	EIA/TIA RS485, RS422, RS232
LEDs	Power, FX Link, DI, DO, Test
Power Input	Card : 12VDC Standalone : AC, DC options

Power Consumption < 5W

Dimensions 155 x 88 x 23mm (D x W x H)

Weight 120g


Temperature 0 ~ 50°C (Operating), -10 ~ 70°C (Storage)

Humidity 10~90% non-condensing

Certification CE, FCC, LVD, RoHS

MTBF 65,000 hrs (25°C)

In-band Managed RS485/422/232 Media Converter



Distributed by:



45 Beechwood Dr., North Andover, MA 01845
www.L-com.com
Fax: 978-689-9484
E-mail: sales@L-com.com
Toll Free: 1-800-343-1455

FRM220-Serial can be inserted in any FRM220 chassis.

Ordering Information

FRM220-□□□□□ Optional card
Serial

Example: FRM220-Serial-S