

18x16x8" UL Listed 120 VAC Weatherproof Enclosure

NB181608-100-UL

Features

- UL® Listed Molded Fiberglass Reinforced Polyester (FRP) indus Fully gasketed raised lid & integral mounting flange trial Enclosure
- · Stainless steel quick release latches with padlock hasps
- NEMA Type 4 / IP66 rated

- Features aluminum mounting plate with surge protected duplex 120 VAC Outlets

Applications

- Remote Wireless LAN WiFi equipment installations
- Indoor and outdoor installations
- · Rapid Deployment Installations

- · Corrosive environments & hotspot applications
- · Protection of equipment from theft or damage

Description

The NB181608-100-UL is approved and listed with UL, meeting the stringent requires for Communication Enclosure System 40XX. The UL listing number is E326684. Use this enclosure when UL Listed products are required by the project. Other UL Listed enclosures are available in many popular features.

Size

Outer Height Outer Width Outer Depth	19.5 in 17.5 in 10 in	[495.3 mm] [444.5 mm] [254 mm]
Inner Height Inner Width Inner Depth	17.7 in 15.7 in 8.4 in	[449.58 mm] [398.78 mm] [213.36 mm]
Weight	19 lbs	[8.62 kg]

Enclosure Material Fiberglass Reinforced Polyester (FRP)

Environmental Specifications

Temperature Rating	-50 to +150°C
Ingress Protection (IP) Rating	IP66

18x16x8" UL Listed 120 VAC Weatherproof Enclosure from L-com has same day shipment for domestic and International orders. Our portfolio includes coaxial cable assemblies, connectors, adapters and custom products as well as lightning and surge protectors, NEMA rated enclosures, and an RF product line which includes antennas, amplifiers, passive, and active components. Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 18x16x8" UL Listed 120 VAC Weatherproof Enclosure NB181608-100-UL

URL: https://www.l-com.com/nema-enclosures-18x16x8-ul-listed-120-vac-weatherproof-enclosure-p.aspx

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.

