

# 14x10x6 Inch Weatherproof ABS Economy Enclosure with Universal Plastic Mounting Plate - Model: NBE141006-KIT03

## **Applications**

- Remote Wireless LAN WiFi equipment installations
- Indoor and outdoor installations
- Rapid deployment installations
- Corrosive environments & hotspot applications
- Protection of equipment from theft or damage

#### **Features**

- Injection molded UV protected light-weight
  ABS resin
- Molded quick release latches and a separate padlock hasp
- NEMA Type 3, 3X and IP55 / IP67 rated
- Fully gasketed raised lid
- Plastic mounting plate with universal hole matrix (no drilling needed)

### Description

The box is a rugged, lightweight weatherproof economy enclosure that is ideal for both indoor and outdoor applications. Constructed from injection molded ABS resin, it is well suited for a wide range of temperature or harsh environments. The mounting holes are molded into the enclosure permitting it to be wall mounted as well as on a flat surface. The raised lid features a 2-part molded hinge and molded quick release latches with a locking hasp on the lid. The raised lid is fully gasketed. The enclosure comes with a removable plastic mounting plate,

which has molded in screw attachment grid for easy mounting of hardware and components. The enclosure material is UV stabilized and comes in neutral light gray color.

The NBE141006-KIT03 is ideal for custom applications, which may require special modifications to the enclosure. Molded in bosses inside the enclosure are used for the mounting plate. The NBE141006-KIT03 is designed for use as electrical and electronic box in many environments including factories and processing plants; municipal and state government installations; retail, wholesale, warehouse and commercial facilities. These enclosures are also suited use as an instrument enclosure in both indoor and outdoor applications.





## **Specifications**

Enclosure Material	UV Protected ABS
Enclosure Color	Neutral Light Gray
Weight	4.20 lbs (1.91 kg)
Outside Dimensions (max)	14.56 x 10.56 x 6.0 in. (370 x 268 x 152 mm)
Plastic Mounting Plate	12.5 x 8.5 in. (Molded in screw attachment grid)
Inside Dimensions	13.63 x 9.67 x 5.35 in. (346 x 245 x 136 mm)
Flame Rating	UL 94-HB
RoHS Compliant	Yes