

# 18"x16"x8" Weatherproof Industrial Enclosure w/Non-Metallic Hinges, Corner Screws and Blank Aluminum Mounting Plate - Model: NBN181608-KIT

### Applications

- Wireless LAN WiFi equipment installations
- Indoor and outdoor installations
- Industrial control equipment installations
- High temperature or corrosive environments
- Hydraulic or pneumatic control installations

#### **Features**

- Rugged FRP Material with gasketed lid
- Stainless steel cover screws
- Non-metallic hinges

contemporary appearance.

- UL/CSA/NEMA/IP rated
- Includes blank aluminum mounting plate



#### Description

The NBN series is a UL/CSA® Listed rugged weatherproof enclosure that is ideal for both indoor and outdoor applications. Constructed from molded halogen free self extinguishing fiberglass reinforced polyester (FRP), it is well suited for high temperature or corrosive environments. The integral mounting flange allows it to be wall mounted as well as on a flat surface without the need for extra mounting hardware. The fully gasketed lid features two stainless steel captive screws and two non-metallic hinges that secure the cover to the base by means of two threaded brass inserts contained in the base that provide a weather-proof seal protecting the contents inside. The light grey color of the NBN series is cleaner, cooler and aesthetically pleasing. Users can enjoy the physical benefits of better heat reflection and better UV resistance due to the lighter color. The contoured body provides an attractive and

The NBN series is ideal for custom applications, which may require special modifications to the enclosure. Contact L-com with your custom requirements and let us provide it for you. Integral mounting stand-offs inside the enclosure can be used for mounting plates. Blank and custom mounting plates are available from L-com.

The NBN181608-KIT includes a Blank Aluminum Mounting Plate permitting free form layout of equipment. The Enclosure and Mounting Plate combination is ideal for custom applications. Mounting stand-offs inside the enclosure are used to secure the Mounting Plate.





**Ribbed Cover Corners** 



Molded Mounting Flanges





## Specifications

## **Enclosure Specifications**

Halogen free, self extinguishing fiberglass reinforced polyester (FRP)
Light Grey (RAL 7036)
16.4 lbs (7.44 kg)
17.31 x 19.31 x 9.58 in (440 x 490 x 243mm)
16.00 x 18.00 x 8.69 in (406 x 457 x 221mm)
Continuous: -58°F to 302°F (-50°C to 150°C) Momentary exposure up to 392°F (200°C).
Yes
Yes
Type 3, 3R, 3S, 4, 4X, 12 and 13
IP66-11

\*Ratings prior to modifications

## **Mounting Plate Specifications**

Plate Material	Aluminum
Dimensions	16.88 x14.88 in. (429 x 378 mm)



L-com, Inc. 50 High St., West Mill, 3<sup>rd</sup> Floor, Suite #30 North Andover, MA 01845 www.L-com.com E-mail: sales@L-com.com Phone: 1-800-343-1455 Fax: 1-978-689-9484 © L-com, Inc. All Rights Reserved. L-com Global Connectivity and the L-com logo are registered marks.