

18x16x10 Polycarbonate Weatherproof Outdoor IP24 NEMA 3R Enclosure, 120VAC Mount Plate Vented Lid Dark Gray

NEMA Enclosures Technical Data Sheet

Features

- High-Impact, UV Resistant Polycarbonate (Dark Gray)
- Stainless steel latches with padlock eye
- NEMA Type 3R / IP24 rated

Applications

- Remote Wireless LAN WiFi equipment installations
- Indoor and outdoor installations
- Rapid Deployment Installations

- Fully gasketed vented lid with filters & user installed wall mounting brackets
- Features aluminum mounting plate with surge protected duplex 120 VAC outlets
- Corrosive environments & hotspot applications
- Protection of equipment from theft or damage

Description

The box is a rugged weatherproof enclosure that is ideal for both indoor and outdoor applications. Constructed from High-Impact, UV Resistant Polycarbonate material that provides superior durability to impacts and ease of modification while maintaining minimum weight. It is well suited for high temperature or corrosive environments. The lid includes two vents with installed rain guards and filters. The included wall mount brackets come uninstalled and bagged with their hardware inside of the enclosure. Once the brackets are installed the enclosure can be mounted directly to any flat wall surface provided proper screws are used into secure studs. The brackets, once installed, also allow you to use our HGX-PMT pole mount kits. The lid features a non-metallic hinge system that allows for quick removal & can be reattached just as quickly without the need for any tools. The enclosure comes with a pair of stainless-steel latches with padlock eyes allowing you to secure the enclosure from tampering. The enclosure comes in a Dark Gray (Pantone 422C)

Mounting Plate

The aluminum mounting plate included with the NBPC181610-10V features standard surge protected duplex 120 VAC outlets and a terminal block for easy hook up to externally provided line power. The enclosure also features holes for two N-Bulkhead lightning protectors or connectors, a grounding lug and cable conduit connector.

The HGX-PMT series of pole mounting kits allow the populated enclosure to be securely mounted to a variety of different size poles.

Compatible versions include HGX-PMT13, HGX-PMT16, HGX-PMT28, HGX-PMT29, HGX-PMT30 & HGX-PMT33

Size		
Outer Height	18.9 in	[480.06 mm]
Outer Width	16.8 in	[426.72 mm]
Outer Depth	11.3 in	[287.02 mm]
Inner Height	18.2 in	[462.28 mm]
Inner Width	16.2 in	[411.48 mm]
Inner Depth	9.7 in	[246.38 mm]
Weight	17.8 lbs	[8.07 kg]
Enclosure Material	Polycarbonate	
Environmental Specifications		
Temperature Rating	-40° to 265° F [-40° to 129° C]	
NEMA Rating	3R	
Ingress Protection (IP) Rating	IP24	

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 18x16x10 Polycarbonate Weatherproof Outdoor IP24 NEMA 3R Enclosure, 120VAC Mount Plate Vented Lid Dark Gray NBPC181610-10V



NBPC181610-10V



18x16x10 Polycarbonate Weatherproof Outdoor IP24 NEMA 3R Enclosure, 120VAC Mount Plate Vented Lid Dark Gray



NEMA Enclosures Technical Data Sheet

Compliance Certifications

UL Listed

No

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 18x16x10 Polycarbonate Weatherproof Outdoor IP24 NEMA 3R Enclosure, 120VAC Mount Plate Vented Lid Dark Gray NBPC181610-10V

URL: https://www.l-com.com/nema-enclosures-18x16x10-polycarbonate-weatherproof-nema-3r-enclosure-120vac-mountplate-vented-lid-dark-gray-p.aspx



NBPC181610-10V



NBPC181610-10V CAD Drawing 18x16x10 Polycarbonate Weatherproof Outdoor IP24 NEMA 3R Enclosure, 120VAC Mount Plate Vented Lid Dark Gray υ ഫ Contectivity NORTH ANDOVER, MA ∢ ENCL PC 18x16x10" w/Vent Lid & 120VAC Mount Plate 19.68 [499.9] NBPC181610-10V DATE 5/16/19 18.74 [476.0] ENCLOSURE 2X 316 SS LATCH, Ø 3/8" PADLOCK EYE 43321 **DH** The second È De. -9.78[248.4] e മ ONFIGURATION DETAILS OF INDIMENSIONED FEATURES MAY VARY 05/14/19 2 INITIAL RELEASE COLOR VARIATIONS MAY OCCUR REV ß മ UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES (mn ANGULAR TOLERANCES: DIMENSIONAL TOLERANCES: ...X = ±.01 [2.54] .XX = ±.01 [.25] .XXX = ±.005 [.13] ć 18.91 [480.3] 18,16 [46].4] 16.88 [428.6] 4 LID NOT SHOWN IN THIS VIEW FOR CLARITY -12.00[304.8] 2X MTG SLOTS -[Z.EOE] 99.11 Ð 16.91 [429.5] 16.16[410.6] 4.88 377.8 8.62[218.9] \bigcirc -[E:901]61.4 **Đ**ệ s [S.65]44.I 10.00[254.0]2X MTG HOLES-1/2" CONDUIT CONNECTOR 0 ц .62 -.95 -2.85 **GROUND LUG** 11.30[287.0]-10.12[257.0]-12.47 [316.8] 5.74[145.7] 4.38[111.1] ċ 3.38 [85.7] COMPONENT ON-BACK OF PLATE DO NOT DRILL -2X FILTER ENCLOSURE MATERIAL-LIGHT GRAY (PANTONE 422C) HIGH-MACT, UV RESISTANT POLYCARBONATE.
TEMPERATURE RANGE: 40°F 10.286°F
CABINETS ARE MAINTENANCE FREE AND CORROSION RESISTANT.
ALALIDMENSIONS FOR REFERENCE ONLY.
ALL DMENSIONS FOR REFERENCE ONLY. THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF LECOM, INC. LANY REPRODICTIONS IN PAPER OR WHOLE WITHOUTHE WRITTEN PERAMISION OF LECOM, INC. IS PROHIBITED. Ø.63[15.9] 2X VENT COVER DETAIL A 2 PLACES VIEW B-B 58 14.7 ω NOTES: 1818

υ

∢